

## 0.6 Symmetrical Cable (Pairing Stranded)

### Description

1/0.60 tinned copper conductor, insulated foam PE(skin-foam-skin), pairing with AL/polyester foil shield, tinned copper drain wire, PVC jacket

### Construction

TYPE	PAIR	CONDUCT O.D. (mm)	INSULATION O.D. (mm)	UNIT SHEATH O.D. (mm)	OUTER JACKET O.D. (mm)
SEYVP (V) 0.6-1P	1	1/0.6	1.5	-	3.9±0.2
SEYVP (V) 0.6-2P	2			3.9±0.2	9.0±0.3
SEYVP (V) 0.6-8P	8			3.9±0.2	12.8±0.3

(V) --- indicated PVC unit sheathing.

### Characteristic

NOM. CAPACITANCE (pF/m)	NOM. IMPEDANCE @1MHz (Ω)	ATTENUATION @1MHz (dB/100m)
≤ 45	120±10%	≤ 1.8

### Color

PAIR	COLOR CODE		PAIR	COLOR CODE		PAIR	COLOR CODE		PAIR	COLOR CODE	
	A	B		A	B		A	B		A	B
1	white	blue	3	white	green	5	white	gray	7	red	orange
2	white	orange	4	white	brown	6	red	blue	8	red	green